

TERMORESISTENTE KLL 125

Tubo in tessuto poliestere spalmato di PVC con spirale in acciaio zincato inserita tra i due strati di tessuto, per condizionamento, aspirazione di fumi e aria calda.



SUPERFICI LISCE
SMOOTH SURFACE

★ ★



FLESSIBILITÀ
FLEXIBILITY

★ ★ ★ ★ ★



RESISTENZA ALL'ABRASIONE
ABRASION RESISTANCE

★ ★



TEMPERATURA D'IMPIEGO
TEMPERATURE RANGE

-5°C + 80°C
per breve tempo fino a +110°C
for a short time up to +110°C



RESISTENZA CHIMICA
CHEMICAL RESISTANCE

PVC table



RESISTENZA ALLO SCHIACCIAMENTO
CRUSHING RESISTANCE

★ ★ ★



AUTOESTINGUENZA
FLAME RETARDANT

DM 26.06.1984 con metodi di prova
UNI 8457-8757/A1-9174-9174/A1.
Italian Ministerial Decree 26.06.1984 with test
methods UNI 8457 - 8757/A1 - 9174 - 9174/A1.



Spirale in acciaio galvanizzato
Galvanised steel spiral

Tessuto in poliestere
rivestito in PVC
PVC coated
Polyester textile

913068



Hose made of polyester textile coated with PVC with galvanised steel spiral embedded between two layers of textile, for air-conditioning, suction of fumes and hot air.

Ø NOMINALE Ø NOMINAL	Ø NOMINALE Ø NOMINAL	Ø INTERNO Ø I.D.	Ø ESTERNO Ø O.D.	SPESORE PARETE WALL THICKNESS	RAGGIO CURVATURA BENDING RADIUS	PASSO SPIRALE SPIRAL PITCH	Ø FILO Ø SPIRAL	SOTTOVUOTO VACUUM	LUNG. ROTOLI COIL LENGTH
inch	mm	mm	mm	mm	mm	mm	mm	m H ₂ O	m
2	40	41	44	0,22	20	20	0,8	1	12
2 1/2	51	51	54	0,22	25	20	0,8	0,95	12
	63	63	66	0,22	31	20	0,8	0,9	12
3	70	70	73	0,22	35	20	0,8	0,85	12
	76	76	79	0,22	36	20	0,8	0,8	12
	82	82	85	0,22	41	20	0,8	0,75	12
3 1/2	89	89	92	0,22	44	20	0,8	0,7	12
4	102	102	105	0,22	51	25	1	0,65	12
	108	108	111	0,22	54	25	1	0,6	12
	114	114	117	0,22	57	25	1	0,55	12
	121	121	124	0,22	60	25	1	0,5	12
5	127	127	130	0,22	63	25	1	0,45	12
	133	133	136	0,22	66	25	1	0,4	12
	140	140	143	0,22	70	25	1	0,38	12
6	152	152	156	0,22	76	32	1,4	0,35	12
	160	161	165	0,22	80	32	1,4	0,32	12
	165	165	169	0,22	82	32	1,4	0,3	12
	178	178	182	0,22	89	32	1,4	0,25	12
8	203	203	207	0,22	101	32	1,4	0,2	12
9	228	228	232	0,22	114	32	1,4	0,15	12
10	254	254	258	0,22	127	40	1,6	0,12	12
	279	279	283	0,22	139	40	1,6	0,1	12
12	304	304	308	0,22	152	40	1,6	0,05	12
	330	330	334	0,22	165	40	1,6	0,03	12
14	355	355	359	0,22	177	40	1,6	0,02	12
16	406	406	410	0,22	203	40	1,6	0,01	12
18	457	457	462	0,22	228	40	1,8	0,0005	12
20	508	508	513	0,22	254	40	1,8	0,0004	12
22	558	558	563	0,22	279	40	1,8	0,0003	12
25	610	610	615	0,22	305	40	1,8	0,0002	12

