



EXHAUST TUBE



10.5001.

Polygonal stripwound galvanized steel exhaust tube, interlocked, medium pitch

#	inch	 mm	 mm	thickness of strip mm	width of strip mm	 mm	 kg/m
10.5001.032	1.1/4"	32,0	35,0	0,30	16,0	135	0,07
10.5001.035	1.3/8"	35,0	38,0	0,30	16,0	145	0,08
10.5001.040	1.1/2"	40,0	43,5	0,30	16,0	165	0,10
10.5001.045	1.3/4"	45,0	48,0	0,30	16,0	168	0,12
10.5001.050	2"	50,0	54,5	0,30	16,0	170	0,21
10.5001.055	2.3/16"	55,0	59,5	0,30	16,0	215	0,25
10.5001.060	2.3/8"	60,0	64,5	0,30	16,0	235	0,27
10.5001.065	2.1/2"	65,0	69,5	0,30	16,0	245	0,40
10.5001.070	2.3/4"	70,0	74,5	0,30	16,0	255	0,49
10.5001.075	3"	75,0	78,5	0,30	16,0	265	0,73
10.5001.080	3.3/16"	80,0	83,5	0,30	16,0	280	0,92
10.5001.085	3.3/8"	85,0	89,5	0,30	16,0	315	1,06
10.5001.090	3.5/8"	90,0	94,5	0,30	16,0	350	1,60
10.5001.095	3.3/4"	95,0	100,0	0,40	24,0	550	2,22
10.5001.100	4"	100,0	105,0	0,40	24,0	555	2,49
10.5001.110	4.3/8"	110,0	115,0	0,40	24,0	565	4,30
10.5001.115	4.5/8"	115,0	120,0	0,40	24,0	570	6,60
10.5001.120	4.3/4"	120,0	125,0	0,40	24,0	575	2,22
10.5001.125	5"	125,0	130,0	0,40	24,0	590	2,49
10.5001.130	5.3/16"	130,0	135,0	0,40	24,0	625	4,30
10.5001.150	6"	150,0	155,0	0,40	24,0	655	6,60

INNER TUBE: galvanized steel medium pitch, polygonal cross-section

APPLICATION: steam, chemicals, oxygen, thermofluid, naphta, cryogening

TEMPERATURE RANGE: -50°C to +250°C

VERSIONS: Stainless steel on demand